

FLEXIBLE CONTROL CABLES

CC 500 Flexible control cable with numbered conductors

-J VDE-Reg.-Nr. 7000 CC 500 50 x 0,5 mm² CE



VDE CE

A
9

Marking for CC 500 02005005:

SAB BRÖCKSKES · D-VIERSEN · ÖZ-J VDE-Reg.-Nr. 7000 CC 500 50 x 0,5 mm² CE

CC 500 is a multi-conductor, flexible power and control cable designed for use in all electrical equipment in dry, damp and wet conditions. Recommended applications include machine tools, assembly lines, control systems, data processing equipment, CNC machining centers, connections between control panels and machines, grinding machines and bottling equipment.

Construction:

Conductor:	bare copper strands acc. to DIN VDE 0295 class 5 + IEC 60228 class 5 + HD 383 class 5
Insulation:	PVC, TI2 acc. to DIN VDE 0281 part 1 + HD 21.1
Color code:	black conductors with consecutive numbers acc. to DIN VDE 0293 + HD 186; green-yellow earth wire from 3 conductors
Stranding:	in layers
Jacket material:	PVC, TM2 acc. to DIN VDE 0281 part 1 + HD 21.1
Jacket color:	gray

Outstanding features:

- flexible
- numbered conductors
- small bending radius

Technical data:

Nominal voltage:	U ₀ /U 300/500 V
Testing voltage U:	3000 V acc. to DIN VDE 0472 part 508
Min. bending radius	
<i>fixed installation:</i>	< 12 mm = 3 x O.D. > 12 mm = 4 x O.D.
<i>free movement:</i>	< 12 mm = 5 x O.D. > 12 mm = 6 x O.D.
Radiation resistance:	8 x 10 ⁷ cJ/kg
Temperature range	
<i>static:</i>	-40/+70 °C
<i>flexing:</i>	+5/+70 °C
Burning characteristics:	flame retardant and self-extinguishing acc. to IEC 60332-1
Oil resistance:	acc. to internal standard, see page L/23
Chem. resistance:	see page L/9

item no.	no. of conductors incl. ground	nominal outer-ø inch	nominal outer-ø mm	cable weight ≈ lbs/mft	item no.	no. of conductors incl. ground	nominal outer-ø inch	nominal outer-ø mm	cable weight ≈ lbs/mft	item no.	no. of conductors incl. ground	nominal outer-ø inch	nominal outer-ø mm	cable weight ≈ lbs/mft
▶ 20 AWG (17/32) • 0.50 mm²					▶ 19 AWG (23/32) • 0.75 mm²					▶ 18 AWG (30/32) • 1.00 mm²				
02000205	2	0.201	5.1	25	02000207	2	0.224	5.7	32	02000210	2	0.232	5.9	36
02000305	3	0.213	5.4	29	02000307	3	0.244	6.2	40	02000310	3	0.252	6.4	45
02000405	4	0.228	5.8	35	02000407	4	0.264	6.7	48	02000410	4	0.276	7.0	55
02000505	5	0.256	6.5	43	02000507	5	0.287	7.3	56	02000510	5	0.307	7.8	68
02000705	7	0.280	7.1	54	02000707	7	0.323	8.2	74	02000710	7	0.335	8.5	86
02000805	8	0.327	8.3	67	02000807	8	0.378	9.6	91	02000810	8	0.390	9.9	106
02000905	9	0.346	8.8	74	02000907	9	0.402	10.2	102	02000910	9	0.425	10.8	122
02001005	10	0.362	9.2	79	02001007	10	0.417	10.6	107	02001010	10	0.433	11.0	127
02001205	12	0.374	9.5	89	02001207	12	0.429	10.9	122	02001210	12	0.445	11.3	142
02001405	14	0.390	9.9	99	02001407	14	0.449	11.4	136	02001410	14	0.476	12.1	164
02001605	16	0.417	10.6	115	02001607	16	0.480	12.2	157	02001610	16	0.500	12.7	183
02001805	18	0.441	11.2	127	02001807	18	0.508	12.9	173	02001810	18	0.535	13.6	208
02002105	21	0.488	12.4	151	02002107	21	0.563	14.3	205	02002110	21	0.591	15.0	244
02002505	25	0.535	13.6	175	02002507	25	0.614	15.6	238	02002510	25	0.646	16.4	284
02003005	30	0.551	14.0	200	02003007	30	0.642	16.3	280	02003010	30	0.669	17.0	328
02003405	34	0.602	15.3	229	02003407	34	0.701	17.8	318	02003410	34	0.728	18.5	374
02004005	40	0.650	16.5	268	02004007	40	0.748	19.0	367	02004010	40	0.783	19.9	437
02004205	42	0.650	16.5	278	02004207	42	0.748	19.0	380	02004210	42	0.783	19.9	455
02005005	50	0.713	18.1	326	02005007	50	0.827	21.0	452	02005010	50	0.862	21.9	532
02006105	61	0.764	19.4	355	02006107	61	0.886	22.5	540	02006110	61	0.929	23.6	644
02006505	65	0.803	20.4	416	02006507	65	0.941	23.9	584	02006510	65	0.976	24.8	688
02008005	80	0.874	22.2	505	02008007	80	1.012	25.7	699	02008010	80	1.063	27.0	835

Continued on next page



FLEXIBLE CONTROL CABLES

CC 500 Flexible control cable with numbered conductors

VDE CE



D-VIERSEN · ÖZ-J VDE-Reg.-Nr. 7000 CC 500 50 x 0,5 mm² CE

Marking for CC 500 02005005:

SAB BRÖCKSKES · D-VIERSEN · ÖZ-J VDE-Reg.-Nr. 7000 CC 500 50 x 0,5 mm² CE

CC 500 is a multi-conductor, flexible power and control cable designed for use in all electrical equipment in dry, damp and wet conditions. Recommended applications include machine tools, assembly lines, control systems, data processing equipment, CNC machining centers, connections between control panels and machines, grinding machines and bottling equipment.

Construction:

Conductor:	bare copper strands acc. to DIN VDE 0295 class 5 + IEC 60228 class 5 + HD 383 class 5
Insulation:	PVC, TI2 acc. to DIN VDE 0281 part 1 + HD 21.1
Color code:	black conductors with consecutive numbers acc. to DIN VDE 0293 + HD 186; green-yellow earth wire from 3 conductors
Stranding:	in layers
Jacket material:	PVC, TM2 acc. to DIN VDE 0281 part 1 + HD 21.1
Jacket color:	gray

Technical data:

Nominal voltage:	U ₀ /U 300/500 V
Testing voltage U:	3000 V acc. to DIN VDE 0472 part 508
Min. bending radius <i>fixed installation:</i>	< 12 mm = 3 x O.D. > 12 mm = 4 x O.D.
<i>free movement:</i>	< 12 mm = 5 x O.D. > 12 mm = 6 x O.D.
Radiation resistance:	8 x 10 ⁷ cJ/kg
Temperature range <i>static:</i> <i>flexing:</i>	-40/+70 °C +5/+70 °C
Burning characteristics:	flame retardant and self-extinguishing acc. to IEC 60332-1
Oil resistance:	acc. to internal standard, see page L/23
Chem. resistance:	see page L/9

Outstanding features:

- flexible
- numbered conductors
- small bending radius

item no.	no. of conductors incl. ground	nominal outer-ø inch	nominal outer-ø mm	cable weight ≈ lbs/mft	item no.	no. of conductors incl. ground	nominal outer-ø inch	nominal outer-ø mm	cable weight ≈ lbs/mft	item no.	no. of conductors incl. ground	nominal outer-ø inch	nominal outer-ø mm	cable weight ≈ lbs/mft
▶ 16 AWG (27-29/30) • 1.50 mm²					▶ 14 AWG (46/30) • 2.50 mm²					▶ 10 AWG (78/28) • 6.00 mm²				
02000215	2	0.264	6.7	48	02000225	2	0.319	8.1	72	02000360	3	0.476	12.1	192
02000315	3	0.280	7.1	58	02000325	3	0.339	8.6	89	02000460	4	0.520	13.2	237
02000415	4	0.311	7.9	73	02000425	4	0.374	9.5	112	02000560	5	0.587	14.9	298
02000515	5	0.339	8.6	87	02000525	5	0.417	10.6	138	02000760	7	0.646	16.4	390
02000715	7	0.378	9.6	116	02000725	7	0.457	11.6	177	▶ 8 AWG (77/26) • 10.00 mm²				
02000815	8	0.441	11.2	141	02000825	8	0.543	13.8	220	02000461	4	0.673	17.1	403
02000915	9	0.480	12.2	157	02000925	9	0.587	14.9	247	02000561	5	0.760	19.3	504
02001015	10	0.488	12.4	165	02001025	10	0.598	15.2	258	02000761	7	0.835	21.2	659
02001215	12	0.504	12.8	190	02001225	12	0.618	15.7	296	▶ 6 AWG (119/26) • 16.00 mm²				
02001415	14	0.535	13.6	218	02001425	14	0.654	16.6	341	02000462	4	0.831	21.1	617
02001615	16	0.563	14.3	245	02001625	16	0.689	17.5	384	02000562	5	0.929	23.6	765
02001815	18	0.602	15.3	278	02001825	18	0.736	18.7	431	02000762	7	1.024	26.0	1004
02002115	21	0.665	16.9	327	02002125	21	0.823	20.9	515	▶ 4 AWG (196/26) • 25.00 mm²				
02002515	25	0.728	18.5	383	02002525	25	0.898	22.8	597	02000463	4	1.004	25.5	966
02003015	30	0.760	19.3	450	▶ 12 AWG (52/28) • 4.00 mm²					02000563	5	1.126	28.6	1212
02003415	34	0.827	21.0	511	02000340	3	0.402	10.2	132	02000763	7	1.244	31.6	1587
02004015	40	0.890	22.6	599	02000440	4	0.445	11.3	166	▶ 2 AWG (280/26) • 35.00 mm²				
02004215	42	0.890	22.6	622	02000540	5	0.496	12.6	205	02000464	4	1.161	29.5	1334
02005015	50	0.976	24.8	732	02000740	7	0.547	13.9	269	02000564	5	1.295	32.9	1669
02006115	61	1.051	26.7	884	▶ 1 AWG (400/26) • 50.00 mm²					02000764	7	1.433	36.4	2190
02006515	65	1.114	28.3	954	02000465	4	1.335	33.9	1824	▶ 1 AWG (400/26) • 50.00 mm²				
02008015	80	1.201	30.5	1148										

Other dimensions and colors are possible on request.

