

FLEXIBLE CONTROL CABLES

also available with black, red and orange conductors and black or orange jacket

CC 600 blue Oil resistant 90°C flexible control cable with blue conductors



2587 90°C 600V CSA AWM I/II A/B 90°C 600V FT 1

02084010 40 x 1,0 mm² CC 600 blue 18 AWG/40c 02081840 VDE-Reg.-Nr. 7000 AWM Style 2587 90°C 600V CSA AWM I/II A/B 90°C 600V FT 1 FT2 CE

CC 600 blue is a multi-conductor, 600 V, 90°C, UL, CSA and VDE approved, oil resistant flexible control cable. The reduced outer diameter permits easy handling and installation in confined areas. Our specially designed PVC jacket passes the stringent requirements of the VDE test 0281 part 1 and HD 21.1 oil test providing the best oil resistance available for a PVC jacket. CC 600 blue control cables are designed for use in all electrical equipment in dry, damp and wet conditions. Recommended applications are machine tools, control systems, assembly lines, CNC machining centers, grinding machines, bottling equipment, data processing equipment and connections between control panels and machines.

A
2

Construction:

Conductor:	bare copper strands acc. to DIN VDE 0295 class 5 + IEC 60228 class 5 + HD 383 class 5
Insulation:	PVC, TI2 acc. to DIN VDE 0281 part 1 + HD 21.1
Color code:	blue conductors with consecutive numbers acc. to DIN VDE 0293 + HD 186; green-yellow earth wire from 3 conductors
Stranding:	in layers
Jacket material:	PVC, TM5 acc. to DIN VDE 0281 part 1 + HD 21.1
Jacket color:	gray

Outstanding features:

- UL and CSA approved
- high mechanical loading capacity
- oil resistant

Technical data:

Nominal voltage:	DIN VDE Uo/U 300/500 V	UL+CSA 600 V
Testing voltage U:	3000 V acc. to DIN VDE 0281 part 2 + HD 21.2	
Min. bending radius <i>fixed installation:</i>	< 12 mm = 3 x O.D. > 12 mm = 4 x O.D.	
<i>free movement:</i>	< 12 mm = 5 x O.D. > 12 mm = 6 x O.D.	
Radiation resistance:	8 x 10 ⁷ cJ/kg	
Temperature range <i>static:</i> <i>flexing:</i>	DIN VDE -40/+70 °C +5/+70 °C	UL+CSA: up to +90°C
Burning characteristics:	flame retardant and self-extinguishing acc. to IEC 60332-1, UL VW1, CSA FT1 and FT2	
Oil resistance:	very good - TM5 acc. to DIN VDE 0281 part 1 + HD 21.1	
Chem. resistance:	see page L/9	

item no.	no. of conductors incl. ground	nominal outer-Ø inch	nominal outer-Ø mm	cable weight = lbs/mft
▶ 20 AWG (17/32) • 0.50 mm²				
02082002	2	0.209	5.3	27
02082003	3	0.220	5.6	32
02082005	5	0.264	6.7	48
02082007	7	0.283	7.2	58
02082008	8	0.335	8.5	77
02082010	10	0.370	9.4	85
02082012	12	0.382	9.7	96
02082014	14	0.398	10.1	108
02082016	16	0.429	10.9	126
02082018	18	0.449	11.4	139
02082025	25	0.547	13.9	190
02082030	30	0.563	14.3	218
02082034	34	0.614	15.6	251
02082040	40	0.665	16.9	296
02082061	61	0.780	19.8	424
▶ 18 AWG (30/32) • 1.00 mm²				
02081802	2	0.236	6.0	37
02081803	3	0.252	6.4	46
02081805	5	0.307	7.8	70
02081807	7	0.335	8.5	87
02081808	8	0.390	9.9	106
02081810	10	0.433	11.0	125
02081812	12	0.445	11.3	142

item no.	no. of conductors incl. ground	nominal outer-Ø inch	nominal outer-Ø mm	cable weight = lbs/mft
▶ 18 AWG (30/32) • 1.00 mm²				
02081814	14	0.476	12.1	165
02081818	18	0.535	13.6	209
02081825	25	0.646	16.4	286
02081830	30	0.669	17.0	331
02081834	34	0.728	18.5	380
02081840	40	0.783	19.9	447
02081861	61	0.933	23.7	654
▶ 16 AWG (27-29/30) • 1.50 mm²				
02081602	2	0.264	6.7	48
02081603	3	0.280	7.1	58
02081605	5	0.339	8.6	90
02081607	7	0.378	9.6	116
02081608	8	0.441	11.2	149
02081610	10	0.488	12.4	167
02081612	12	0.504	12.8	191
02081614	14	0.535	13.6	220
02081616	16	0.563	14.3	249
02081618	18	0.602	15.3	282
02081625	25	0.728	18.5	386
02081630	30	0.760	19.3	453
02081634	34	0.827	21.0	519
02081640	40	0.902	22.9	620
02081661	61	1.051	26.7	891

item no.	no. of conductors incl. ground	nominal outer-Ø inch	nominal outer-Ø mm	cable weight = lbs/mft
▶ 14 AWG (46/30) • 2.50 mm²				
02081402	2	0.319	8.1	73
02081403	3	0.339	8.6	89
02081405	5	0.417	10.6	141
02081407	7	0.457	11.6	179
02081408	8	0.543	13.8	233
02081410	10	0.598	15.2	260
02081412	12	0.618	15.7	299
02081418	18	0.736	18.7	440
02081425	25	0.909	23.1	612
▶ 12 AWG (52/28) • 4.00 mm²				
02081203	3	0.402	10.2	132
02081205	5	0.496	12.6	209
02081207	7	0.547	13.9	271
▶ 10 AWG (78/28) • 6.00 mm²				
02081003	3	0.476	12.1	193
02081004	4	0.520	13.2	239
02081005	5	0.587	14.9	303
▶ 8 AWG (77/26) • 10.00 mm²				
02080804	4	0.701	17.8	423
02080805	5	0.780	19.8	527
▶ 6 AWG (119/26) • 16.00 mm²				
02080604	4	0.850	21.6	635
▶ 4 AWG (196/26) • 25.00 mm²				
02080404	4	1.051	26.7	1006
▶ 2 AWG (280/26) • 35.00 mm²				
02080204	4	1.197	30.4	1368

Other dimensions and colors are possible on request.

